

Details:

- 1) Windows CE 6.0 system. 8-inch high-definition digital touch screen Original HannStar, Huayang temperature loaders.
 - 2) supports DVD, VCD, CD, CD-R, CD-RW, MP3, DIVX, MP3, MP4, MP5 (RM, RMVB (1280 * 720P)), SVCD, DVD-9, AVI and JPEG, BMP, PNG, TIFF, JIF
 - 3) Built-in Bluetooth: support handsfree call, dial-up and calls automatically, support A2DP
 - 4) Built-in AM / FM radio, 6-disc virtual function and RDS optional
 - 5) iPod connectivity and support PIP (Picture in Picture) function, BT Phonebook
 - 6) CMMB, DVB-T, ATSC, ISDB-T (optional)
 - 7) Dual Zone (radio or television play DVD, and navigation)
 - 8) Support iPod List
 - 9) Built-in 4X45W hi-fi amplifier: international professional BBE sound processing to strengthen audio ambience and good decorative effect, make music more gentle
 - 10) Full function infrared remote control
 - 11) is equipped with reverse video signal input, can support a variety of reversing camera, automatic switch to reverse
 - 12) Electronic and mechanical anti-shock system
 - 13) Support TOMTOM, IGO8, ROUTE66, Navitel / guides, and maps.
 - 14) Languages: English, Russian, Portuguese, Chinese (both), Arabic, Spanish, Turkish, Vietnamese and so on. More menu language can be customized.
- CD supportSVCD / DVCD / DVD / VCD / CD / CD-R / CD-RW / JPEG / WMA / MP3 / MP4 / DIVX / AAC / / MP5

Total

Supply voltage DC 9V-16V

Overload4Ω

Maximum power output45W × 4

The sound control7db

Bass 20HZ

Treble 20KHZ

Output portAudio: 4 independent output channels

Video: a composite video output channels

Enter portAudio: 2 independent input channels

Video: 3 composite video input channels

Video FeaturesVideo output level: 1.0 Vp-p (75Ω overload)

Video Features and Implication: 20HZ-20KHZ (+1 dB)

Temperature -10 °C + 60 °C

Humidity15-75% (non-chilled water)

VCD / CD section

Video systemAuto / NTSC / PAL

S / N (signal to noise ratio) 60 db (1KHZ0 db)

Resolution55dB

Frequency response20Hz-20KHZ

Dynamic range80dB

Distortaion0.4%

DVD section

Video systemAuto / NTSC / PAL

S / N (signal to noise ratio) 75 db (1 KHZ0 db)

Resolution60dB

Frequency response20Hz-20KHZ

Dynamic range 80dB

Distortion 0.4%

FM section

Frequency range 87.5-108.0MHz

Practical sensitivity 22dB

The downward sensitivity 9dB

S / N (signal to noise ratio) 60 db (1KHz 0 db)

Resolution 32dB

Frequency response 40Hz-13KHz

Medium frequency 10.7MHz of

AM section

Frequency range 522-1620KHz

The downward sensitivity 35dB

Practical sensitivity 28dB

S / N (signal to noise ratio) 45 db (1 KHz 0 dB)

Medium frequency 450MHz of

Frequency response 40Hz-2.3KHz

Platform: A4 ARM11 radio tuner: SI 4745 MCU: SIRF AT840

ROM: 512M RAM: 128M

[More Toyota products, please click](#)