

規格

- 1 Windows CE 6.0 / 6.2
 - 2 DVD / VCD / CD / CD-R / CD-RW / MP3 / DIVX / MP3 / MP4 / MP5 / RM / RMVB / 1280 * 720P / SVCD / DVD-9 / AVI / JPEG / BMP / PNG / TIFF / JIF
 - 3 AAC / A2DP
 - 4 AM / FM 6 RDS
 - 5 iPod / PIP / BT
 - 6 CMMB / DVB-T / ATSC / ISDB-T
 - 7 DVD
 - 8 iPod
 - 9 4X45W BBE
 - 10
 - 11
 - 12
 - 13 TOMTOM / IGO8 / ROUTE66 / Navitel /
 - 14
- support SVCD / DVCD / DVD / VCD / CD / CD-R / CD-RW / JPEG / WMA / MP3 / MP4 / DIVX / AAC / / MP5

電源

- DC 9V-16V
- Overload 4Ω
- output 45W × 4
- control 7db
- 20HZ
- 20KHZ
- portAudio 4
- 1
- portAudio 2
- 3

- Features Video 1.0 Vp-p 75Ω
- 20HZ-20KHZ +1
- 10°C +60°C
- Humidity 15-75

VCD / CD

- system Auto / NTSC / PAL
- S / N 60 1KHZ 0
- Resolution 55dB
- response 20Hz-20KHZ
- range 80dB
- Distortaion 0.4

DVD

- system Auto / NTSC / PAL
- S / N 75 1KHZ 0
- Resolution 60dB
- response 20Hz-20KHZ
- range 80dB
- Distortaion 0.4

FM

- range 87.5-108.0MHZ

FM sensitivity 22dB
FM sensitivity 9dB
S / N ratio 60dB 1KHz
Resolution 32dB
Frequency response 40Hz-13KHz
Frequency 10.7MHz

AM
range 522-1620KHz
sensitivity 35dB
sensitivity 28dB
S / N ratio 45dB 1KHz
frequency 450MHz
response 40Hz-2.3KHz

Platform A4 ARM11
SI 4745 MCU
SIRF AT840
ROM 512M RAM 128M

Navigation

