

Hannstar HD original digital touch screen, Foryou high temperature loader
 Support MP4, MP5(720P RM/RMVB), SVCD, DVD, AVI, JPEG, BMP, etc.
 Built-in Bluetooth, Support BT phonebook with name searching function.
 Bulit-in AM/FM Radio, RDS stations
 Ipod ready, support Ipod List
 Support Digital TV, CMMB, ISDB-T, DVB-T and ATSC(optional)
 Dual Zone (listen to music or radio while in gps navigation)
 Support 6 CDC, 3G usb port for internt
 Bulit 4*45W hi-fi amplifier
 Accurate navigation, support TOMTOM, IGO8, ROUTE66, NAVITEL etc.
 Multilanguages: English, Russian, Portuguese, Spanish, Turkish, Hebrew, Arabic etc. More languages can be customized.

Disc support	DVD/VCD/CD/CD-R/CD-RW/JPEG/WMA/MP3/MP4/DIVX/MP4/MP5
--------------	---

General

Power voltage	DC 9V-16V
Overload	4Ω
Max power output	45W x 4 7db
Tone control	Bass 20Hz Treble 20KHz
Output port	Audio: 4 independent output channels Video: 1 Composite video output channels
Input port	Audio: 2 independent input channels Video: 3 composite video input channels
Video Features	Video output level: 1.0 VP-P(75Ω overload) Video features: 20Hz-20KHz(±1dB)
Temperature	-10°C+60°C
Humidity	15-75% (no water frozen)

□

DVD PART

Video system	Auto/NTSC/PAL
S/N(signal to noise ratio)	75dB(1KHz 0dB)
Resolution	60dB
Frequency response	20Hz-20KHz
Dynamic range	80dB
Distortaion	0.40%

□

FM PART

Frequency range	87.5-108.0MHz
Practical sensitivity	22dB
Down sensitivity	9dB
S/N(signal to noise ratio)	60dB (1KHz 0dB)
Resolution	32dB
Frequency response	40Hz -13KHz

Medium frequency	10.7MHz
AM PART	
Frequency range	522-1620KHz
Down sensitivity	35dB
Practical sensitivity	28dB
S/N(signal to noise ratio)	45dB (1KHz 0dB)
Medium frequency	450MHz
Frequency response	40Hz-2.3KHz
	