

supportSVCD / DVCD / DVD / VCD / CD / CD-R / CD-RW / JPEG / WMA / MP3 / MP4 / DIVX / AAC // MP5

DC 9V-16V

Overload4Ω

output45W × 4

control7db

20Hz

20KHZ

PortAudio : 4

: 2

PortAudio : 2

: 3

FeaturesVideo : 1.0 VP-P (75Ω)

features : 20Hz-20KHZ (1)

-10 °C ~ + 60 °C

Humidity15-75 %

VCD / CD

systemauto / NTSC / PAL

S / N (1 kHz) 60dB (0dB)

Resolution55dB

response20Hz-20KHZ

range80dB

Distortaion0.4 %

DVD

systemauto / NTSC / PAL

S / N (1 kHz) 75dB (0dB)

Resolution60dB

response20Hz-20KHZ

range80dB

Distortaion0.4 %

FM

range87.5-108.0MHz

sensitivity22dB

sensitivity9dB

S / N (1 kHz) 60dB (0dB)

Resolution32dB

response40Hz-13KHz

frequency10.7MHz

range522-1620KHz

sensitivity35dB

sensitivity28dB

S / N (1 kHz) 45dB (0dB)

frequency450MHz

response40Hz-2.3KHZ

Plarform : A4 ARM11 RADIO Tunner : SI 4745 MCU : SIRF AT840

