

Disc supportSVCD / DVCD / DVD / VCD / CD / CD-R / CD-RW / JPEG / WMA / MP3 / MP4 / DivX / AAC / / MP5

Power supply

Power supply DC 9V-16V

Overload4Ω

Power output45W × 4

Control7db

20Hz 100%

20KHZ

PortAudio Output: 4 channels

PortAudio: 2 channels

PortAudio: 3 channels

FeaturesVideo resolution: 1.0 Vp-P (75Ω)

features: 20Hz-20kHz (1 %)

temperature -10 °C + 60 °C

Humidity15-75% (non-condensing)

VCD / CD player

systemauto / NTSC / PAL

S / N (1 kHz 0 dB) 60 dB

Resolution55dB

response20Hz-20KHZ

range80dB

Distortaion0.4%

Power supply

systemauto / NTSC / PAL

S / N (1 kHz 0 dB) 75 dB

Resolution60dB

response20Hz-20KHZ

range80dB

Distortaion0.4%

Power supply

range87.5-108.0MHz

sensitivity22dB

sensitivity9dB

S / N (1 kHz 0 dB) 60 dB

Resolution32dB

response40Hz-13KHz

frequency10.7MHz

Am player

range522-1620KHz

sensitivity35dB

sensitivity28dB

S / N (1 kHz 0 dB) 45 dB

frequency450MHz

response40Hz-2.3KHZ

Plarform: A4 ARM11 Tunner: SI 4745 MCU: SIRF AT840

□□□□□□□□□□:

- 

11)

13) [TOMTOM](#), [iGO8](#) [Route66](#) [Map](#)

[illegible]