

Disc supportSVCD / DVCD / DVD / VCD / CD / CD-R / CD-RW / JPEG / WMA / MP3 / MP4 / DivX / AAC / / MP5

Power supply

Power supply voltageDC 9V-16V

Overload4Ω

Power output45W × 4

Control7db

20Hz 100%

20KHZ

portAudio Output: 4 ports

portAudio: 2 ports

portAudio: 2 ports

portAudio: 3 ports

FeaturesVideo: 1.0 Vp-P (75Ω)

features: 20Hz-20kHz (1 %)

-10 °C + 60 °C

Humidity15-75% (non-condensing)

VCD / CD

systemAuto / NTSC / PAL

S / N (1KHz 0 dB) 60 dB

Resolution55dB

response20Hz-20KHZ

range80dB

Distortaion0.4%

systemAuto / NTSC / PAL

S / N (1 KHz 0 dB) 75 dB

Resolution60dB

response20Hz-20KHZ

range80dB

Distortaion0.4%

range87.5-108.0MHz

sensitivity22dB

sensitivity9dB

S / N (1KHz 0 dB) 60 dB

Resolution32dB

response40Hz-13KHZ

frequency10.7MHz

Am

range522-1620KHz

sensitivity35dB

sensitivity28dB

S / N (1 KHz 0 dB) 45 dB

frequency450MHz

response40Hz-2.3KHZ

Plarform: A4 ARM11 Tunner: SI 4745 MCU: SIRF AT840

[illegible]